



## PRBMA06

## **Description**

PRBMA06 are a cost effective Bluetooth audio module, supporting Bluetooth 2.1 (audio), Bluetooth 4.x (BLE) and SPP at the same time. They also supports AT-Command for controlling and configuration purpose.

Beside Bluetooth audio, PRBMA05/06 also supports SD-card mode, and such application can be used in speaker application.

PRBMA05 and PRBMA06 are fully pin compatible, and PRBMA06 contains metal shielding for application that requires EMC insurance.

PRBMA06 are firmware pre-programmed, user can simply use it after power up without any firmware development.

PRMBA06 is FCC, CE, TELEC \*certified module, which reduces customer's resource for qualification and allows product to be time to market.

• 14.94 x 19.6 x 3 mm

Protocol support:

HFPV1. A2DPV1.2 \

AVRCPV1.5 AVCTPV1.2 \

**AVDTPV1.2** 

Audio source:

BT or SD-CARD


- Operating voltage: 3.3-4.2VDC
- Power consumption:
  - 3.5mA before connection
  - 20mA after connection
- Operation temperature:

-40 to 80°C

- RF distance: 15m (max)
- Sensitivity: -87dBm

\* in process





Dimension (mm)

url: www.k-sol.com.hk facebook: ksolutionhk twitter: K-Solution Consulting